MCS - Mixe Communication Solutions

Wireless Voice & Data Solutions

AS5401/2V Light

.....the GSM-Gateway which will grow together with your needs

MCS had developped a unique concept in order to have the best solution for all Partners in the chain. The AS5401/2V Light is a GSM-Gateway that has especially been designed to meet the requirements of those companies who want to save from fixed to mobile. The AS5401/2V Light is the perfect step towards enormous savings. Therefore the return on investment of this product is extremely fast.

Many companies will find out that they want to use more functionalities.This is the reason that we can upgrade remotely all our products with more functionalities, including the unique GSM Mobility Extension feature in order to make the mobile phone act as an internal extension.

You, as MCS-reseller, can offer this upgrade and thus earn more money with the same Gateway.

Wireless Modules by Siemens embedded

Pay no more then you use

Remote upgrade to more features

Earn more money with after sales

Supports all BRI-PABX's

Supports all GSM-networks

Personalised Gateway possible

Order number

P108562 – AS5401/2V Light – GSM-ISDN Interface with 2 GSM-modules, 0dB fixed antenna, power supply, synchronisation option. Targeted at outgoing calls.

108570 – Pro upgrade

For interesting conditions, we can make the AS5401/2V Light a personalised GSM-Gateway, with your own logo and company name. Call us for the conditions.

Features	AS5401/2V Light	Pro-upgrade
GSM-channels	2	2
GSM-channels when using GME-feature (GME=GSM Mobility Extension)		1
Connection	BRI, TE/NT/ QSIG	BRI, TE/NT/ QSIG
Antenna combiner	1:2	1:2 or 1:4
Antenna	1x 0dB	1x 0dB
Slimline desktop model	x	x
SIM-cards per channel	1	1
Remote configuration	x	x
Remote tracing	x	x
Remote upgrading	x	x
Callback		x
Call barring	X	X
Call diversion	X	X
Unanswered call setup		x
Statistics		X
Extended LCR		x
White/blacklist		x
Dialing-in, via DTMF	X, to one number	X, unlimited
Import function for GSM-numbers		x
GSM Network control		x
Voice, melodies, tunes		x
Network blocking		x
Possibility to program voice		x
SMS monitoring		x
Sync	X	x
Selective CLI surpression		x
Time quote per GSM-channel		
Overflow when GSM-network blocked	X	x
Backup battery possible		x
Configuration SW included	X	x
Conference call PBX ->GSM		x
Explicit call transfer PBX->GSM		x
GME: Call Hold GSM->PBX		x
GME: Explicit call transfer GSM->PBX		x
GME: Call swap GSM->PBX		x

Kiotoweg 719-721, NL- 3047 BG Rotterdam
Tel: +31-10-4375555 Fax: +31-10-4375656
www.mcs-nl.com info@mcs-nl.com

Pegasuslaan 5, B-1831 Brussel
Tel: +32-2-7164837 Fax: +32-2-7164108
www.mcs-be.com info@mcs-be.com